

BananaPi R64

- [Hardware](#)
 - [storage](#)
 - [gpio](#)
- [uboot](#)
 - [2014-04 in my repo](#)
 - [official 2014-04](#)
- [kernel](#)
 - [my 4.19 my 5.4-rc](#)
 - [official 4.19](#)
- [images](#)
 - [debian 8 Image](#)
 - [ubuntu 16.4 + armbian buster](#)
- [links](#)
 - Developer documents: [mt7622](#) [mt7531](#)
 - [schematics](#)
 - http://wiki.banana-pi.org/Banana_Pi_BPI-R64
 - http://wiki.banana-pi.org/Getting_Started_with_R64

```
root@bpi-r64:~# dpkg-reconfigure tzdata
root@bpi-r64:~# date -s "2019-02-03 11:24:00 CET"

#remove existing ip-addr for wan (optional) and add new
root@bpi-r64:~# curip=$(ip addr show eth1 | grep inet | awk '{print $2}')
root@bpi-r64:~# ip addr del $curip dev eth1
#add new one
root@bpi-r64:~# ip addr add 192.168.0.18/24 dev eth1
root@bpi-r64:~# ip link set eth1 down
root@bpi-r64:~# ip link set eth1 up
root@bpi-r64:~# ip route add default via 192.168.0.10
root@bpi-r64:~# echo "nameserver 192.168.0.10">/etc/resolv.conf
```

From:
<http://fw-web.de/dokuwiki/> - **FW-WEB -Wiki**

Permanent link:
<http://fw-web.de/dokuwiki/doku.php?id=bpi-r64:start>

Last update: **2020/08/29 17:14**

