BananaPi R64

- Hardware
  - storage
  - gpio
- uboot
  - 2014-04 in my repo
  - official 2014-04
- kernel
  - my 4.19 my 5.4-rc
  - official 4.19
- images
  - debian 8 Image
  - ubuntu 16.4 + armbian buster
- links
  - Developer documents: mt7622 mt7531
  - shematics
  - http://wiki.banana-pi.org/Banana_Pi_BPI-R64
  - http://wiki.banana-pi.org/Getting_Started_with_R64

```
root@bpi-r64:~# dpkg-reconfigure tzdata
root@bpi-r64:~# date -s "2019-02-03 11:24:00 CET"

#remove existing ip-addr for wan (optional) and add new
root@bpi-r64:~# curip=$(ip addr show eth1 | grep inet | awk '{print $2}')
root@bpi-r64:~# ip addr del $curip dev eth1
#add new one
root@bpi-r64:~# ip addr add 192.168.0.18/24 dev eth1
root@bpi-r64:~# ip link set eth1 down
root@bpi-r64:~# ip link set eth1 up
root@bpi-r64:~# ip route add default via 192.168.0.10
root@bpi-r64:~# echo "nameserver 192.168.0.10">/etc/resolv.conf
```

From:
http://www.fw-web.de/dokuwiki/ - **FW-WEB Wiki**

Permanent link:
http://www.fw-web.de/dokuwiki/doku.php?id=bpi-r64:start

Last update: **2023/06/08 17:06**