

# NFTables

Example from eric with combined ipv4+ipv6 (latter untested):

<https://github.com/ericwoud/buildR64arch/blob/main/rootfs/etc/nftables.conf>

forwarding: <https://www.eukhost.com/kb/how-to-enable-ip-forwarding-on-linux-ipv4-ipv6/>

```
apt install nftables
echo 1 > /proc/sys/net/ipv4/ip_forward

nft list ruleset
nft add table nat
nft add chain ip nat prerouting { type nat hook prerouting priority 100 \; }
nft add chain ip nat postrouting { type nat hook postrouting priority 100 \; }
nft add rule nat postrouting masquerade

#portforwarding
nft add rule nat prerouting iif lan1 tcp dport 443 dnat 192.168.0.10:443 #
ip needs to be routed to other interface then in-interface (here lan1)
```

named priorities (>=0.9.1):

[https://thermalcircle.de/doku.php?id=blog:linux:nftables\\_packet\\_flow\\_netfilter\\_hooks\\_detail](https://thermalcircle.de/doku.php?id=blog:linux:nftables_packet_flow_netfilter_hooks_detail)

## links

- <https://developers.redhat.com/blog/2017/01/10/migrating-my-iptables-setup-to-nftables/>
- [https://wiki.gentoo.org/wiki/Nftables/Examples#Basic\\_routing\\_firewall](https://wiki.gentoo.org/wiki/Nftables/Examples#Basic_routing_firewall)
- <https://wiki.nftables.org/wiki-nftables/index.php>
- [https://wiki.nftables.org/wiki-nftables/index.php/Quick\\_reference-nftables\\_in\\_10\\_minutes](https://wiki.nftables.org/wiki-nftables/index.php/Quick_reference-nftables_in_10_minutes)

## hwnat

<https://github.com/frank-w/BPI-R2-4.14/commits/5.12-hnat>

ipv6 mangle does not support hnat (connection reset!)

to get hwnat working, a newer version of nftables is needed than available in debian buster

<https://github.com/frank-w/nftables-bpi>

compiled: <https://drive.google.com/drive/folders/1hajKvqQa96WRrAy52fQX90i59I1s0h-i?usp=sharing>

basic IPv4 Ruleset:

```
flush ruleset
table ip filter {
```

```

flowtable f {
    hook ingress priority filter + 1
    devices = { lan3, lan0, wan }
    flags offload;
}
chain input {
    type filter hook input priority filter; policy accept;
}

chain output {
    type filter hook output priority filter; policy accept;
}

chain forward {
    type filter hook forward priority filter; policy accept;
    ip protocol { tcp, udp } flow add @f
}
}
table ip nat {
    chain post {
        type nat hook postrouting priority filter; policy accept;
        oifname "wan" masquerade
    }

    chain pre {
        type nat hook prerouting priority filter; policy accept;
    }
}

```

basic v6 Ruleset (hw-nat for IPv6 not supported):

```

flush ruleset
table ip6 filter {
    flowtable f {
        hook ingress priority 1
        devices = { lan3, lan0, wan }
        flags offload;
    }
    chain input {
        type filter hook input priority 0; policy accept;
    }

    chain output {
        type filter hook output priority 0; policy accept;
    }

    chain forward {
        type filter hook forward priority 0; policy accept;
#        ip6 nexthdr { tcp, udp } flow add @f
    }
}

```

```
table ip6 nat {  
    chain post {  
        type nat hook postrouting priority 0; policy accept;  
        #oifname "wan" masquerade  
    }  
  
    chain pre {  
        type nat hook prerouting priority 0; policy accept;  
    }  
}
```

test it:

```
nft -f nft-nat-flowoffload.nft  
#generate traffic from client e.g. iperf3  
cat /sys/kernel/debug/mtek_ppe/entries
```

IPv6-Setup

```
#!/bin/bash  
#on main-router:  
#ip -6 route add fd00:a2::/64 via fd00:a::12  
#ip -6 route add 2001:470:xxxx:a2::/64 via 2001:470:xxxx::12  
  
ip -6 addr add fd00:a::12/64 dev wan  
ip -6 addr add fd00:a2::12/64 dev lan3  
  
ip -6 addr add 2001:470:xxxx::12/64 dev wan  
ip -6 addr add 2001:470:xxxx:a2::12/64 dev lan3  
  
sysctl -w net.ipv6.conf.all.forwarding=1
```

From:  
<http://fw-web.de/dokuwiki/> - **FW-WEB Wiki**



Permanent link:  
<http://fw-web.de/dokuwiki/doku.php?id=en:bpi-r2:network:nftables>

Last update: **2023/09/10 16:40**